



---

**Product Quotation**

**Prepared For:  
Levi Beachy**

**City of Tillamook  
Tillamook OR 97141**



**Prepared By:  
CHRIS MCKINNEY  
PACIFIC JCB - PORTLAND  
PORTLAND OR 97230  
mobile:**

Image is for indicative purpose only and may not represent exact equipment being quoted



## Standard Equipment

Standard Equipment and Features & Benefits related to this product are subject to change without notice

ENGINE	4.4L (268CID) 74 SAE Gross hp, JCB Ecomax T4F diesel engine with no DPF, centrifugal dry type dual stage air cleaner. Fuel filter with water separator, 1000 CCA battery; variable speed hydraulically driven fan which can either manually or automatically reverse to clean out debris around the radiator and oil cooler.
TRANSMISSION	EH (Electo-Hydraulic) Controls with hydrostatic transmission. Standard two (2) speed transmission provides a low range of 0 - 4.8 mph and a high range of 0 - 7.8 mph in both forward and reverse. Standard Creep speed provides operation from 0 to 1/2 of full speed for special applications.
RUBBER TRACKS	Fitted with 17.7" wide tracks provide a machine width of 78" and a ground bearing pressure of 5.0 psi.
BRAKES	Machine braking provided through the hydrostatic transmission. Parking brake consists of multiple disc, oil immersed, spring applied hydraulic release that provides a fail safe with the engine off. Electrically activated through a switch on the instrument panel or by raising seat bar.
ELECTRICAL	Meets IP69 (external) IP67 (internal) water ingress standard. Worklights, 2 Front and 1 Rear, Reverse Alarm, Horn, and 12V Accessory Socket.
INSTRUMENTS	Audible and visual warning systems, right and left side mounted instrument panels. Standard electronic throttle control with foot throttle.
CAB	SAE certified ROPS/FOPS, left side entry. Units are equipped with a suspension seat with adjustable arm pods, an operator restraint interlock for safety. Right Hand glass standard on all units.
HYDRAULICS	24gpm @ 3335psi standard flow and 33gpm @ 3335psi Highflow auxiliary hydraulics
LOADER	Rated Operating Capacity of 3600 lbs, Radial Lift Loader Design provides a radial lift path, and with a two stage telescopic boom, a hinge pin height of 159" (13'-3") and 96" (8') of forward reach. Auxiliary hydraulic circuit and high flow are standard for operation of hydraulic powered attachments. All machines are equipped with: Automatic Attachment Leveling System, Smooth Ride System (SRS), a Sealed Electric Power Quick Hitch, ISO/Dual Hand Pattern Changer and Hydraulic Float.
SERVICEABILITY	Cab tilts forward to provide further access to the hydraulic components. The bucket tilt (crowd) cylinder has been repositioned inside the boom, thereby allowing the cab to be tilted for service access without raising the boom. Rear door provides access to engine bay and daily maintenance and check points.





---

## Features and Benefits

Standard Equipment and Features & Benefits related to this product are subject to change without notice

---

4.4L JCB T4F EcoMAX TCAE-55kw engine

No need for after treatment or regeneration due to HP being below 74 HP threshold for emissions

---

Servo Controls with hydrostatic transmission. Standard Creep Speed

Multiple speeds to accommodate variety of applications. Standard two speed with travel Speeds of 7.3 to 13.5 mph with 14x17.5 size tires and 6.8 to 12.4 mph with 12 x 16.5 size tires in both forward and reverse.

---

Machine braking provided through the hydrostatic transmission

Less wear parts and fail safe when engine is off

---

SAE certified ROPS/FOPS, left side entry

Safest skid steer on the market with side door entry

---

Meets IP69 water ingress standard

Protects worklights - 2 Front and 2 Rear, Reverse Alarm, Horn, and 12V Accessory Socket

---

24gpm @ 3335psi standard flow.  
Optional 33gpm

High flow capability when the boom is retracted and standard flow capability when the boom is extended. Provides versatility of attachments and applications.

---

Rated Operating Capacity of 3200 lbs retracted and 1200lbs extended, Radial Lift Loader Design

The extension of the boom provides a vertical lift and a radial lift in one machine

---

Standard Powered Quick Hitch

Variety accommodates all users in a variety of applications

---

Cab tilts forward

Provides easier maintenance, provides optional control style, better material retention in the bucket, and bi-directional parallel lift for fork applications

---





**Prepared For:**  
 Levi Beachy  
 City of Tillamook  
 2211 3rd Street Suite A  
 Tillamook OR 97141

phone:503-812-8804  
 fax:(503) 842-3445  
 lbeachy@tillamookor.gov

**Dealer Information**  
 PACIFIC JCB - PORTLAND  
 13805 NE SANDY BLVD  
 PORTLAND OR 97230  
 phone:(503) 287-6700  
 www.fsforegon.com

**Prepared By:**  
 CHRIS MCKINNEY  
 cmckinney@pacificjcb.com  
 mobile:  
 Quote Date: 06/22/20  
 Valid Until: 07/22/20  
 Quotation Reference: 267463

**Model: 3TS-8T**

**Qty: 1**

**Equipment Description**

3TS-8T TELESKID S/5 NA TRACK  
 450mm(17.7 Inch ) Wide Rubber Track  
 Cab Standard Tracked With Heat And A/c Option Teleskid  
 JCB Controls With 7 Way Joysticks And Attachment Harness  
 No Bucket Option  
 Track Teleskid Std Features - USA  
 High Flow Hydraulics (33.1 Gpm / 3335 Psi) (135 Lpm / 230 Bar)  
 With Creep Speed  
 332/x3180 78 Inch Gp Bucket (1980Mm) Includes Boce 881H303

Equipment Total	79,830.40
Less Trade In	8,000.00
Total Less Trade	71,830.40
 Total Customer Sale Price	 71,830.40

**Optional Extras** (Optional Extras are not included in the totals)

JCB 333/X4383 78 inch Brush Cutter - High Flow	7,213.00
JCB 332/L3342 Pallet Fork Frame, Load Backrest and 48 inch Tines (6000 lb. Lift Capacity)	988.00
JCB 332/L4036 76 inch Heavy Duty Scrap Grapple (With Solid Floor)	4,151.00
JCB 332/L7244 Rock Saw 18 inch Depth - High Flow	14,374.00
JCB 332/X4294 Stump Grinder - 30 inch Wheel Diameter / High Flow	8,105.00
JCB 332/ X4282 84 inch Vibratory Roller - Smooth Drum	9,047.00
JCB 332/L3339 78 inch - 6 in 1 Multipurpose Bucket (21.7 cu. ft. capacity)	4,163.00

Notes: Sourcewell Contract # 040319-JCB  
 FOB Portland, OR  
 Balance due in full prior to delivery or approved financing  
 Final price includes trade in of JCB 530-70 Telehandler

Customer Acceptance: \_\_\_\_\_ Date \_\_\_\_\_

Dealer \_\_\_\_\_ Date \_\_\_\_\_

